

樹枝粉碎機 WE-M12R



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for utility line clearing, residential tree services, rental yards and municipalities.
- The dual-sided, chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.
- Like all equipment, the M12R is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 12" high throat opening allows for easy feeding of branchy material and reduced saw labor.



Drive Belt Cover

Drive belt inspection cover provides easy access for drive system maintenance.



Hydra-Lift System

The powerful Hydra-Lift™ dual feed wheel compression system with spring-assisted down pressure generates more than 3,300 lb./ft. of combined material pulling force.



360° Swivel Discharge

360° swivel discharge with chip deflectors puts chips right where they're needed without removing the Beaver from the tow vehicle.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 8/28/15

General

Chipping capacity..... 12"
Height..... 8'5"
Width..... 5'11"
Length..... 15'5"
Gross weight (approximate)..... 5,500 lbs.
Suspension..... 6,000 lb. Torflex
Infeed opening..... 60" wide x 31" high
Throat opening..... 15" wide x 12" high
Drum..... 14 1/2" wide x 21 3/8" diameter
Engine... CAT, GM, John Deere, Kubota or Perkins
Horsepower..... 49-130 HP
Fuel capacity..... 24 1/2 gallons
Hydraulic capacity..... 17 gallons
Frame..... 8.2 lb., 6" channel
Tires..... (2) 235/80R16"
Hitch..... 2 1/2" Pintle Ring

Equipment Highlights

14 1/2" wide x 21 3/8" diameter staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided chambered air impeller system
Top and bottom horizontal feed wheels equipped with serrated teeth and knife bars
Reversing automatic feed system
Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
Fuel tank sight gauge, drain plug and shut-off valve
Hydraulic tank shut-off valve, drain plug and clean-out cover
Live hydraulics; ball valve, pump, motor and control valve
3" x 5" tubular steel telescoping drawbar with two 12" extensions

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
Folding infeed tray
Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
Custom paint and logo packages
Bottom Bump Bar
Hydraulic Swivel Discharge
Cone Holder
Flow Control
Axle Options Available
Fender Options Available
Battery Box Options Available



瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街135巷24號
信件請寄：高雄市郵政信箱1394號
Tel：07-7169249 Fax：07-2134620

E-Mail: agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/i-chipper/Index.htm>

Line：weizohu1995 Skype：service450429 QQ：1467808036

Viber: +886972326392 WhatsApp: +886972326392 Wechat: walterhsu1995

樹枝粉碎機 WE-M12R TRACK



BENEFITS

- With its power and easily transportable design, this compact and economical chipper is the ideal unit for right-of-way and utility line clearing, highway clean-ups, residential tree services, rental yards and municipalities.
- The dual-chambered air impeller system increases chip-throwing velocity and reduces dust and material blowback out the infeed to pack more into the chip truck.
- The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.
- Like all equipment, the M12R is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Opening

The 60" wide x 31" high chute opening and 15" wide x 12" high throat opening allows for easy feeding of branchy material and reduced saw labor.



Track Undercarriage

Take the chipper to the material with a two-speed, 72" long x 11" wide track undercarriage and 3.31 PSI ground pressure.



Hydra-Lift System

The powerful Hydra-Lift™ dual feed wheel compression system with spring-assisted down pressure generates more than 3,300 lb./ft. of combined material pulling force.



360° Swivel Discharge

360° swivel discharge with chip deflectors puts chips right where they're needed.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 3/12/15

General

Chipping capacity..... 12"
Height 8'
Width 6'3"
Length 13'9"
Gross weight (approximate) 6,400 lbs.
Infeed opening..... 60" wide x 31" high
Throat opening..... 15" wide x 12" high
Drum 14 1/4" wide x 21 3/8" diameter
Engine CAT or Kubota
Horsepower 84-114 HP
Fuel capacity 24 1/2 gallons
Hydraulic capacity 17 gallons
Frame 2" x 4" tubular

Equipment Highlights

Wireless Remote Control operation with tethered back-up system controls the track functions, feed functions, yoke functions and throttle functions with emergency engine stop
Dual horizontal feed wheel compression system with hydraulic lift assist, spring-assisted down pressure and manually applied hydraulic down pressure at the valve handle
Reversing automatic feed system
Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
Fuel tank sight gauge, drain plug and shut-off valve
Hydraulic tank shut-off valve, drain plug and clean-out cover
Live hydraulics; ball valve, pump, motor, control valve and variable speed flow control

Additional Features

Steel guard enclosing valve bank and automatic feed system components
Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
Custom paint and logo packages
Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
Bottom Bump Bar
Hydraulic Swivel Discharge
Folding Infeed Tray
Flow Control



瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街135巷24號
信件請寄：高雄市郵政信箱1394號
Tel：07-7169249 Fax：07-2134620

E-Mail: agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/i-chipper/Index.htm>

Line：weizohu1995 Skype：service450429 QQ：1467808036

Viber: +886972326392 WhatsApp: +886972326392 Wechat: walterhsu1995