

乘座式割草機

WeMaTra130-140



language



瑋洲企業有限公司 Tel : 07-7169249 Fax : 07-2134620
地址：台灣高雄市前鎮區武德街135巷24號 信件請寄：高雄市郵政信箱1394號

M A D E I N I T A L Y



Ma.Tra.
130
140



MAINTENANCE OF YOUR GREEN SPACE MOVES TO THE NEXT LEVEL

Think more power, more efficiency, more comfort

The **Ma.Tra. 130** and **Ma.Tra. 140** have been developed to effectively respond to the requirements of private owners and professional maintenance workers who need to have machines that are comfortable, performing and safe when mowing and cutting grass and bushes in unkempt areas. Their structure is sturdy and tough and their center of mass is especially low, to allow safe mowing even when working on steep slopes or uneven ground. The efficient hydrostatic drive combined with high-quality engines ensures

the best reliability to these machines, even if they are intensively used. The firm-built heavy duty mower's "low-noise" underbody makes it possible to mow and shred large quantities of grass and shrubs, even ones with much wood, without affecting its performance. The efficient and responsive steering wheel affords the driver narrow turns that, along with driving comfort and the machine's operating speed, make the **Ma.Tra. 130** and **Ma.Tra. 140** the work companion you simply can't do without.





DRIVING POSITION

Top driving comfort with sprung seat and armrests with ergonomic controls.



STABILITY

Low barycenter and tires with slip-proof tread to guarantee ideal stability when working on a slope.

HEAVY DUTY MOWER

Single-blade "low-noise" heavy duty mower: solid and efficient, it yields superb performance, to mow and shred branches up to 15 mm wide.



STEERING

Steering radius of only 485 mm, to mow in cramped spaces and around trees with the greatest ease.

TRASMISSION

Professional Kanzaki hydrostatic transmission of the highest quality, serviceable to guarantee the utmost reliability.

CLUTCH

Electromagnetic PTO clutch with blade brake and automatic release when you need to lift the heavy duty mower off ground, to get past obstacles or bumps.

ENGINE

Honda engine (Ma.Tra. 130) and Briggs & Stratton (Ma.Tra. 140) of the professional series, to provide the best performance and cut down on consumption.



HEAVY DUTY HYDROSTATIC MOWERS MA.TRA. 130 AND MA.TRA. 140 TECHNICAL FEATURES

	130	140
Engine	Honda GXV390, single-cylinder	Briggs & Stratton Vanguard V-Twin OHV, twin cylinder
Power kW / Hp	7,3 / 9,9	11,2 / 15,2
Displacement cc	389	479
Start	electric starter, with 12 V battery	electric starter, with 12 V battery
Fuel tank capacity	9,5 L - reserve tank 1 L	9,5 L - reserve tank 1 L
Consumption L/h	2,5	3,5
Transmission	hydrostatic, single range, lever operated	
Speed km/h	FWD: 0 - 9,5 / REV: 0 - 7,5	
Drive control	lever operated	
Differential	with lock, pedal operated	
Heavy duty mower	single-blade with rear discharge	
Cutting width mm	850	
Cutting height adjustment	6 different cutting positions	
PTO clutch	electromagnetic with blade brake	
Service brakes	on the front wheels	
Parking brake	on the rear wheels	
Driving system	by steering wheel, acting on the front wheels	
Seat	adjustable, sprung, with arm rests	
Tyres	front: 13x5.00-6 rear: 16x6.50-8	
Inner turning diameter mm	970	
Mowing capacity per hour (indicative) mq	4800	6000
Rear tow hook	standard	

DIMENSIONS

Length mm	2000
Width mm	1030
Height mm	960
Weight Kg (with mower)	280



E-Mail:agri-machine@weizhou.com.tw
 Line : weizohu1995 Skype : service450429 QQ : 1467808036
 Viber:+886972326392 WhatsApp:+886972326392 Wechat:walterhsu1995
<http://www.weizhou.com.tw/Agrimachine/import/Lawn%20Tractor/lawnmower-1.htm>