



農業曳引機

WE-240S BT GOLD POWER MINIMAX 機型



SPECIFICATION		DESCRIPTION
ENGINE		240S BT GOLDPOWER MINIMAX
Emission		Stage IIIA
Make / Type		BOZOK ENGINE / 1003D
Number of Cylinders / Aspiration		3 / Turbo Intercooler
Displacement		2990 cm ³
Air Filter		Dry Type
PERFORMANCE		
Maximum Engine Power (ISO)		57 HP (42 kw)
Nominal Engine Speed		2200 d/d (rpm)
Maximum Torque		224 Nm / 1500 d/d (rpm)
CLUTCH		
PTO	Type	Dry Dual Clutch
	Disc Diameter	254 mm – 304 mm (10"-12")
IPTO	Type	Dry Single Clutch
	Disc Diameter	305 mm (12")
STEERING		
Type		Hydrostatic
Maximum Steering Angle		50°
Turning Circle Without Braking		6350
TRANSMISSION		
Type of Transmission		Standard

Gear Option	8 Forward 2 Reverse
Optional Gear Option	N/A
Hareket letimi	Direct
Mechanical 4WD Engagement	
Differantial Lock	Mechanical
Differantial Lock	29 km/h
POWER TAKE-OFF (PTO)	
Mechanical Clutch (PTO)	•
540 rpm PTO Speed @ 1790 rpm	•
Independent Hydraulic Clutch	?/•
Ground Speed PTO	?/•
PTO Power (ISO)	46,5 HP@2250
BRAKES	
Type	Disc Brakes Drum Brakes
Pedals	Classic or Pendant Pedal

HYDRAULIC SYSTEM	
Draft Control	•
Position Control	•
Accuracy Control	•
Maximum Pump Flow	18 lt/dk (lt/min)
Maximum Pump Pressure	210 bar
Maximum Lifting Capacity	2000 kg
External Pump Flow	42lt/dk (lt/min) / 175 barda
Spool Valve	o / •
CAPACITIES	
Fuel Tank	48 lt
Oil Sump	7.5 lt
Coolant	18 lt
Transmission & Hydraulics	36.5 lt
Steering	2 lt

MASSES AND DIMENSIONS

Total Mass with ballast (kg)	2050
Front Masses (kg)	(4x20 Kg) – (Çekili ağırlık 1x36 Kg)
Rear Masses (kg)	(2x45 Kg)
A Front Axle Ground Clearance	510 mm
B Front Track Width	1400 mm
C Overall Width	1620 mm
D Rear Track Width	1300 mm
E Wheelbase	1910 mm
F Rear Overhang	865 mm
G Front Overhang	675 mm
H Overall Length	3450 mm
I Overall Height	2350 mm
J Hood-Top Height	1320 mm
L Folded ROPS Height	1762 mm
K Buffer Ground Clearance	285 mm
M Rear Tow ground Clearance	330 mm
Front Tyres	6.00 - 16
Rear Tyres	13.6/12 - 28



A Division of Ken-Ding Group

瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街 135 巷 24 號

信件請寄：高雄市郵政信箱 1394 號

Tel : 07-7169249 Fax : 07-2134620

Weizhou International Co., Ltd

Address : No. 24, Lane 135 Wu-de St., Kaohsiung City, Taiwan ROC80647

Mailing : P. O. Box 1394 kaohsiung City. Taiwan ROC

Tel : 886-7-7169249 Fax : 886-7-2134620

E-MAIL : agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/Tractor/index-import.htm>

QQ : 1467808036

SKYPE : service450429

LINE : weizhou1995

Wechat : walterhsu1995

Viber : +886972326392

WhatsApp : +886972326392