



## 農業曳引機

WE-BOZOK 275 4X4 (1104-A44 PERKINS UK)機型



| SPECIFICATION                                  |  | DESCRIPTION                                                                                     |
|------------------------------------------------|--|-------------------------------------------------------------------------------------------------|
| PERFORMANCE                                    |  |                                                                                                 |
| Rated Engine Power                             |  | ISO/TR14396<br>75 hp ( 54 kW )                                                                  |
| Max. Torque@1400 rpm<br>Max. PTO Power @ rated |  | 275 Nm                                                                                          |
| engine speed                                   |  | 62.9 hp                                                                                         |
| ENGINE                                         |  |                                                                                                 |
| Type                                           |  | Perkins / 1104A-44                                                                              |
| No. Cylinders                                  |  | 4                                                                                               |
| Injection                                      |  | Direct                                                                                          |
| Capacity                                       |  | 4.4 litre                                                                                       |
| Air Cleaner                                    |  | Dual, Dry Air Cleaner with<br>overbonnet centrifugal<br>pre - cleaner / Oil bath<br>air cleaner |
| Exhaust                                        |  | Vertical                                                                                        |
| ELECTRICS                                      |  |                                                                                                 |
| Alternator / Starter                           |  | 50A/ 3.0kW                                                                                      |
| Lights                                         |  | Headlights, Sidelights,<br>brake lights, direction<br>indicators, rear work lamp                |
| Other                                          |  | Horn, 7- pin trailer socket                                                                     |
| CLUTCH                                         |  |                                                                                                 |

|                                                   |                                                                                             |
|---------------------------------------------------|---------------------------------------------------------------------------------------------|
| Type                                              | Dual Clutch                                                                                 |
| Diameter                                          | 305 X 254 mm                                                                                |
| TRANSMISSION                                      | 8 Forward 2 Reverse<br>Sliding Spur,                                                        |
| POWER TAKE OFF                                    |                                                                                             |
| Type                                              | Dual Clutch, pedal operated                                                                 |
| PTO speed                                         | 540 rev/ min @ 1685<br>engine rev / min or ground speedPTO                                  |
| Shaft Diameter                                    | 35 mm ( 1.38 mm )                                                                           |
| Number of Splines                                 | 6                                                                                           |
| HYDRAULICS                                        |                                                                                             |
| Functions                                         | Draft, Position, and<br>response control                                                    |
| Max. Oil Flow                                     | 16.7 litre / min                                                                            |
| Max.Pressure                                      | 207 bar                                                                                     |
| Max. Lift Capacity at links ends, link horizontal | 2290kg                                                                                      |
| Lower Links                                       | Cat 2 fixed ball ends<br>linkage check chains and<br>stabilisers                            |
| Drawbar                                           | Swinging drawbar                                                                            |
| STEERING                                          |                                                                                             |
| Type                                              | Hydrostatic                                                                                 |
| REARAXLE AND BRAKES                               |                                                                                             |
| Brake Type                                        | Oil-Cooled, disc                                                                            |
| Actuation                                         | Mechanical, independent<br>or locked together                                               |
| Parking Brake                                     | Hand lever operated                                                                         |
| Differential Lock                                 | Mechanical actuation                                                                        |
| OPERATOR AREA                                     |                                                                                             |
| Seat                                              | Spring Suspension                                                                           |
| Fender                                            | Flat Top                                                                                    |
| Tool Box                                          | With optional toolkit                                                                       |
| INSTRUMENTATION                                   |                                                                                             |
| Gauges                                            | Tachometer, fuel gauge,<br>temperature gauge                                                |
| Warnings Lights                                   | Electric charge, low engine<br>oil pressure, direction<br>indicators, main beam,<br>filter, |
| STANDARDWHEELS AND TYRES                          |                                                                                             |

|                                                                 |                        |
|-----------------------------------------------------------------|------------------------|
| Fronts - 2WD<br>4WD                                             | 7.50 – 16<br>12.4x24   |
| Rear - 2WD<br>4WD                                               | 16,9 – 30<br>16,9 – 30 |
| WEIGHTS AND DIMENSIONS                                          |                        |
| With standard wheels and tyres, with fuel, oil and water Weight | 2WD/4WD 2780 kg/3010kg |
| Overall Length                                                  | 2WD/4WD 3.60 m/3.89 m  |
| Width - mininum Height                                          | 1.99 m Overall         |
| over exhaust                                                    | 2.52 m                 |
| over steering wheel                                             | 1.70 m                 |
| Wheelbase – 2WD/4WD m/2.29 m                                    | 2.06                   |
| Turning Circle - less brakes                                    | 2WD/4WD 7.20 m /9.75 m |
| Ground Clearance, under over drawbar                            | 381 mm                 |
| CAPACITIES                                                      |                        |
| Fuel Tank                                                       | 70 litre               |



### A Division of Ken-Ding Group

瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街 135 巷 24 號

信件請寄：高雄市郵政信箱 1394 號

Tel：07-7169249 Fax：07-2134620

Weizhou International Co., Ltd

Address：No. 24, Lane 135 Wu-de St., Kaohsiung City, Taiwan ROC 80647

Mailing：P. O. Box 1394 kaohsiung City. Taiwan ROC

Tel：886-7-7169249 Fax：886-7-2134620

E-MAIL：[agri-machine@weizhou.com.tw](mailto:agri-machine@weizhou.com.tw)

<http://www.weizhou.com.tw/Agrimachine/Tractor/index-import.htm>

QQ：1467808036

SKYPE：service450429

LINE：weizhou1995

Wechat：walterhsu1995

Viber：+886972326392

WhatsApp：+886972326392