



農業曳引機

WE-BOZOK 290 4X2 (1104-A44 PERKINS UK)機型



SPECIFICATION		DESCRIPTION
PERFORMANCE		
Rated Engine Power	ISO /TR 14396 82 hp ISO (61 kW)	
Max. Torque@1400 rpm Max. PTO Power @ rated	294 Nm	
engine speed	75.7 hp	
ENGINE		
Type	Perkins / 1104A-44	
No. Cylinders	4	
Injection	Direct	
Capacity	4.4 litre	
Air Cleaner	Dual, Dry Air Cleaner with overbonnet centrifugal pre - cleaner / Oil bath air cleaner	
Exhaust	Vertical	
ELECTRICS		
Alternator / Starter	50A/ 3.0kW	
Lights	Headlights,Sidelights, brake lights, direction indicators,rear work lamp	
Other	Horn, 7- pin trailer socket	
CLUTCH		
Type	Dual Clutch	

Diameter	305 X 254 mm
TRANSMISSION	8 Forward 2 Reverse Sliding Spur, Optional:12x4 partly synchromesh
POWER TAKE OFF	
Type	Dual Clutch, pedal operated
PTO speed	540 rev/ min @ 1685 engine rev / min or ground speedPTO
Shaft Diameter	35 mm (1.38 mm)
Number of Splines	6
HYDRAULICS	
Functions	Draft, Position, and response control
Max. Oil Flow	16.7 litre / min
Max.Pressure	207 bar
Max. Lift Capacity at linksends, link horizontal	2290 kg
Lower Links	Cat 2 fixed ball ends linkage check chains and stabilisers
Drawbar	Swinging drawbar
STEERING	
Type	Manual /Hydrostatic
REARAXLE AND BRAKES	
Brake Type	Oil-Cooled, disc
Actuation	Mechanical, independent or locked together
Parking Brake	Hand lever operated
Differential Lock	Mechanical actuation
OPERATOR AREA	
Seat	Spring Suspension
Fender	Flat Top
Tool Box	With optional toolkit
INSTRUMENTATION	
Gauges	Tachometer, fuel gauge,temperature gauge
Warnings Lights	Electric charge, low engine oil pressure, direction indicators, main beam, filter, (optional: 4WD, IPTO)
STANDARDWHEELS AND TYRES	
Fronts - 2WD - 4WD	7.50 - 16 12.4 - 24

Rear - 2WD - 4WD	18.4 - 30 18.4 - 30
WEIGHTS AND DIMENSIONS	
With standard wheels and tyres, with fuel, oil and water	
Weight - 2WD/4WD	2880 kg/3010 kg
Overall Length - 2WD/4WD	3.89 m/3.89 m
Width - mininum	2.06 m
Overall Height - over exhaust	2.52 m
Wheelbase - 2WD/4WD	2.29 m/2.29 m
Turning Circle - less brakes 2WD/4WD	2WD/4WD 8.55 m/9,75 m
Ground Clearance, under over drawbar	381mm
over front axle -2WD/4WD	486 mm/395 mm
CAPACITIES	
Fuel Tank	70 litre



A Division of Ken-Ding Group

瑋洲企業有限公司

地址: 台灣高雄市前鎮區武德街 135 巷 24 號

信件請寄: 高雄市郵政信箱 1394 號

Tel : 07-7169249 Fax : 07-2134620

Weizhou International Co., Ltd

Address : No. 24, Lane 135 Wu-de St., Kaohsiung City, Taiwan ROC80647

Mailing : P. O. Box 1394 kaohsiung City. Taiwan ROC

Tel : 886-7-7169249 Fax : 886-7-2134620

E-MAIL : agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/Tractor/index-import.htm>

 QQ : 1467808036

 SKYPE : service450429

 LINE : weizhou1995

 Wechat : walterhsu1995

 Viber : +886972326392

 WhatsApp : +886972326392