

樹枝粉碎機 WE-M18RX



BENEFITS

- Ideal for residential tree services, vegetation management, lot and land clearing, maintenance contractors and municipalities, this chipper combines Morbark strength in a more compact design.
- While retaining an 18" chipping capacity, the M18RX weighs in at less than 10,000 lbs. (GVWR) fully charged with fluids and winch package, eliminating the need for additional transport licensing requirements.
- Infeed is made with 7-gauge (5 mm), XF-100 sides and 3/8" (10 mm) thick, XF-100 floor to increase material tensile strength with lighter weight components.
- Like all equipment, the M18RX is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed

Oversized perimeter opening with large throat opening, radius infeed walls and straight flow through infeed design increases efficiency while reducing infeed wear.



Pivot Assembly

Bearing-style yoke pivot assembly with TorqMax™ drive and Variable Force™ down pressure system increases down pressure efficiency by 25%.



Reversing Auto-feed

The reversing auto-feed system automatically stops forward feed and briefly backs material away from the drum for optimum engine performance while chipping.



Separate Fluid Tanks

7-gauge split fuel and hydraulic reservoirs with shut-off valves reduce risks of vibration damage and cross-contamination while allowing for easy maintenance.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 6/29/15

General

Chipping capacity..... 18"
Height..... 9'4"
Width..... 7'8"
Length (Transport)..... 18'3"
Gross weight (approximate)..... 9,550 lbs.
Suspension..... 10,000 lb. Torflex
Infeed Opening..... 65" wide x 38" high
Throat Opening..... 21" wide x 18 3/4" high
Drum..... 23 1/2" wide x 37 3/8" diameter
Engines... CAT, Cummins, John Deere or Perkins
Horsepower..... 130-170 HP
Fuel capacity..... 44 gallons
Hydraulic capacity..... 26 gallons
Frame..... 8.2 lb., 6" channel
Tires..... (2) 235/75x17 1/2"
Hitch..... 2 1/2" Pintle

Equipment Highlights

Four dual-edged knife staggered-pocket drum with patented EZ Drum removable knife holders, dual-sided, chambered air impeller system and controllable air flow vents
Top 20 1/2" wide horizontal feed wheel equipped with serrated teeth and knife bars
360° manual crank swivel discharge with adjustable height and chip deflectors
Live hydraulic system including: ball valve, pump, motor, and valve bank with additional pre-plumbed valve section for installation of an aftermarket winch package
4" x 6" tubular steel fixed-length drawbar and 3/8" thick safety chains with clasp hooks
Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options Include

ChipSafe® Operator Safety Shield
Winch package: heavy-duty, 5,000 lb. pull capacity with rope and 10' chafe guard
Custom paint and logo packages
Bottom Bump Bar
Hydraulic Swivel Discharge
Cone Holder
Spare Tire/Mount
Folding Infeed Tray
Flow Control
Axle, Fender and Battery Box Options Available



瑋洲企業有限公司

地址：台灣高雄市前鎮區武德街135巷24號
信件請寄：高雄市郵政信箱1394號
Tel：07-7169249 Fax：07-2134620

E-Mail: agri-machine@weizhou.com.tw

<http://www.weizhou.com.tw/Agrimachine/i-chipper/Index.htm>

Line : weizohu1995 Skype : service450429 QQ : 1467808036

Viber: +886972326392 WhatsApp: +886972326392 Wechat: walterhsu1995